

8000 SERIES NVRS AT-A-GLANCE

	32 CHANNEL HYBRID			24 CHANNEL TRIBRID
				
Model Number	8732 R	8532 R	8532 S	8724 V
Base Part Number	28065	28066	28067	9 options**
Total Inputs	32			24
Analog/IP Inputs	16/32			Up to 24 (8 port modules)
PoE Ports	0			Up to 24 (8 port modules)
Channel Licenses Included	32			24
Analog Performance	480 FPS @ 4CIF	240 FPS @ 4CIF		720 FPS @ 1080p
IP Performance (primary plus alternate stream)	96 Mbps			80 Mbps
HD Analog supported formats	N/A			TVI, CVI, AHD
Analog Compression	H.264			H.264
Local Area Network	GigE			GigE
Camera Network	GigE			10/100 Base-T
Analog Resolutions	4CIF/2CIF/CIF			Up to 1080p
IP Resolution	Camera dependent			Camera dependent
Operating System	Embedded Linux			Embedded Linux
Alarms	8 In / 4 Out			2 In / 1 Out
Audio	4 In / 2 Out			4 In / 2 Out
Local Control	Yes (IP Camera Capable)			Yes (IP Camera Capable)
Video Out	HDMI/Composite			HDMI
Max HDDs	4			2
Max HD Storage	Up to 72 TB			36 TB
Storage Redundancy	Mirroring (reduces throughput)			Mirroring (reduces throughput)
Data Ports	4 USB, 1 RS-232, 1 RS-485			Internal 1 (local control mouse), External 2 (video export)
Docking Station	Yes		No	No
Dimensions (H x W x D)	3.1 x 17.4 x 16.0 in (8.0 x 44.2 x 40.6 cm)		3.2 x 16.9 x 16.0 in (8.1 x 43.0 x 40.6 cm)	19.7 x 17.9 x 7.6 in 50 x 45.4 x 19.2 cm)
Environmental	41° to 105°F (5° to 40°C)			41° to 105°F (5° to 40°C)
Power Supply	Internal 115/230 VAC (auto-sensing); 75 W max			External 110/220 VAC (auto-sensing), 1.7A, 50-60Hz
Weight (add 5.5 lbs/2.5 Kg for docking station)	18.5 lbs (8.4 Kg)		13 lbs (5.9 Kg)	23.5 lbs (10.7 Kg)
Battery Backup	Yes			Yes
Mounting Options	Dock, Desk, Wall	Dock, Desk, Wall	Desk, Wall	Wall
Front Panel QR Code*	Yes			Yes
Analytics	Included: Motion Detection; Optional: Camera Obstruction Detection, Field of View Change, Trip Wire, Loitering, Presence Detection			






*The QR Code on the front panel contains useful information about the recorder, such as model number and serial number. When the code is scanned using the March Networks GURU smartphone application, this information allows integrators to easily check warranty status, initiate an express RMA, get in-field diagnostics support, review and change recorder IP addresses, register/unregister from the Enterprise Service Manager, and go through SSH to view storage information.

3-year warranty on all recorders:




- Options for Repair & Return or Advance Replacement
- March Networks incurs all shipping costs—both ways—for AR's
- All recorder components are covered, including HDDs

**	36132	8 PoE Ports
	35972	8 HD Analog Inputs
	35470	16 PoE Ports
	35471	16 HD Analog Inputs
	35473	24 PoE Ports
	35474	24 HD Analog Inputs
	36133	8 PoE Ports, 8 HD Analog Inputs
	35476	8 PoE Ports, 16 HD Analog Inputs
	35477	16 PoE Ports, 8 HD Analog Inputs

8000 SERIES HYBRID NVRS AT-A-GLANCE

	16 CHANNEL HYBRID			16 CHANNEL HYBRID RAID5	
					
Model Number	8716 P	8516 R	8516 S	8516 SR	8516 RR
Base Part Number	34246	28646	28068	35692	35693
Total Inputs	16			16	
Analog/IP Inputs	8/16	16/16		16 (8 port modules)/ 16 (if analog inputs disabled)	
PoE Ports	8	0		0	
Channel Licenses Included	16			16	
Analog Performance	30 FPS @4CIF	240 FPS @ 4CIF		240 FPS @ 4CIF	
IP Performance (primary plus alternate stream)	80 Mbps			80 Mbps	
Analog Compression	H.264			H.264	
Local Area Network	GigE			GigE	
Camera Network	10/100 Base-T	GigE		GigE	
Analog Resolutions	4CIF/2CIF/CIF			4CIF/2CIF/CIF	
IP Resolution	Camera dependent			Camera dependent	
Operating System	Embedded Linux			Embedded Linux	
Alarms	2 In / 1 Out	8 In / 4 Out		4 In / 2 Out	
Audio	2 In / 1 Out	4 In / 2 Out		4 In / 2 Out	
Local Control	Yes (IP Camera Capable)			Yes (IP Camera Capable)	
Video Out	HDMI/Composite			HDMI/Composite	
Max HDDs	2	4		4	
Max HD Storage	Up to 36 TB	Up to 72 TB		Up to 72 TB (54 useable)	
Storage Redundancy	Mirroring (reduces throughput)			RAID5 (reduces throughput during rebuild)	
Data Ports	4 USB, 1 RS-232	4 USB, 1 RS-232, 1 RS-485		4 USB, 1 RS-232, 1 RS-485	
Docking Station	No	Yes	No	No	Yes
Dimensions (H x W x D)	3.6 x 11.3 x 12.0 in (9.18 x 28.7 x 30.6 cm)	3.1 x 17.4 x 16.0 in (8.0 x 44.2 x 40.6 cm)	3.2 x 16.9 x 16.0 in (8.1 x 43.0 x 40.6 cm)	3.2 x 16.9 x 16.0 in (8.1 x 43.0 x 40.6 cm)	3.1 x 17.4 x 16.0 in (8.0 x 44.2 x 40.6 cm)
Environmental	41° to 105°F (5° to 40°C)			41° to 105°F (5° to 40°C)	
Power Supply	External 110/220 VAC (auto-sensing), 60 W max	Internal 115/230 VAC (auto-sensing); 75 W max		Internal 115/230 VAC (auto-sensing); 75 W max	
Weight (add 5.5 lbs/ 2.5 Kg for docking station)	7.8 lbs (3.6 Kg)	18.5 lbs (8.4 Kg)	13 lbs (5.9 Kg)	18.5 lbs (8.4 Kg)	13 lbs (5.9 Kg)
Battery Backup	Yes			Yes	
Mounting Options	Desk, Wall	Dock, Desk, Wall	Desk, Wall	Dock, Desk, Wall	Desk, Wall
Front Panel QR Code*	Yes			Yes	
Analytics	Included: Motion Detection Optional: Camera Obstruction Detection, Field of View Change, Trip Wire, Loitering, Presence Detection			Included: Motion Detection; Optional: Camera Obstruction Detection, Field of View Change, Trip Wire, Loitering, Presence Detection	

8000 SERIES HYBRID NVRS AT-A-GLANCE

	8 CHANNEL HYBRID		4 CHANNEL HYBRID
			
Model Number	8708 S	8508 S	8704 S
Base Part Number	28570	28568	28569
Total Inputs	8		4
Analog/IP Inputs	8/8		4/4
PoE Ports	0		0
Channel Licenses Included	8		4
Analog Performance	240 FPS @ 4CIF	120 FPS @ 4CIF	120 FPS @ 4CIF
IP Performance (primary plus alternate stream)	80 Mbps		80 Mbps
Analog Compression	H.264		H.264
Local Area Network	GigE		GigE
Camera Network	GigE		GigE
Analog Resolutions	4CIF/2CIF/CIF		4CIF/2CIF/CIF
IP Resolution	Camera dependent		Camera dependent
Operating System	Embedded Linux		Embedded Linux
Alarms	2 In / 1 Out		2 In / 1 Out
Audio	2 In / 1 Out		2 In / 1 Out
Local Control	Yes (IP Camera Capable)		No
Video Out	HDMI/Composite		No
Max HDDs	2		2
Max HD Storage	Up to 36 TB		Up to 10 TB
Storage Redundancy	Mirroring (reduces throughput)		Mirroring (reduces throughput)
Data Ports	4 USB, 1 RS-232		2 USB, 1 RS-232
Docking Station	No		No
Dimensions (H x W x D)	3.6 x 11.3 x 12.0 in (9.18 x 28.7 x 30.6 cm)		3.2 x 8.3 x 5.0 in (8.1 x 21.2 x 12.6 cm)
Environmental	41° to 105°F (5° to 40°C)		41° to 105°F (5° to 40°C)
Power Supply	External 110/220 VAC (auto-sensing); 60 W max		External 110/220 VAC (auto-sensing); 20 W max
Weight (add 5.5 lbs/ 2.5 Kg for docking station)	7.3 lbs (3.3 Kg)		3.3 lbs (1.5 Kg)
Battery Backup	Yes		Yes
Mounting Options	Desk, Wall		Desk, Wall
Front Panel QR Code*	Yes		Yes
Analytics	Included: Motion Detection Optional: Camera Obstruction Detection, Field of View Change, Trip Wire, Loitering, Presence Detection		Included: Motion Detection; Optional: Camera Obstruction Detection, Field of View Change, Trip Wire, Loitering, Presence Detection

*The QR Code on the front panel contains useful information about the recorder, such as model number and serial number. When the code is scanned using the March Networks GURU smartphone application, this information allows integrators to easily check warranty status, initiate an express RMA, get in-field diagnostics support, review and change recorder IP addresses, register/unregister from the Enterprise Service Manager, and go through SSH to view storage information.

North America 1 800 563 5564
Latin America +5255 5259 9511
Europe +39 0362 17935
Asia +65 6818 0963
Australia and New Zealand +61 1300 089 419
Middle East and Africa +971 4 399 5525

© 2021 March Networks. All rights reserved. Information in this document is subject to change without notice. MARCH NETWORKS, March Networks Command, March Networks Searchlight, March Networks RideSafe, and the MARCH NETWORKS logo are trademarks of March Networks Corporation. All other trademarks are the property of their respective owners. 060-3172-00-L
marchnetworks.com

